ҚАЗАҚСТАН РЕСПУБЛИКАСЫ
ҰЛТТЫҚ ҒЫЛЫМ АКАДЕМИЯСЫНЫҢ
Әль-фараби атындағы Қазақ ұлттық университетінің

ХАБАРЛАРЫ

ИЗВЕСТИЯ

НАЦИОНАЛЬНОЙ АКАДЕМИИ НАУК
РЕСПУБЛИКИ КАЗАХСТАН
Казахский национальный университет
имени Аль-фараби

NEWS

OF THE NATIONAL ACADEMY OFSCIENCES
OF THE REPUBLIC OF KAZAKHSTAN
Al-farabi kazakh
national university

SERIES
PHYSICO-MATHEMATICAL

2 (324)

MARCH - APRIL 2019

PUBLISHED SINCE JANUARY 1963

PUBLISHED 6 TIMES A YEAR

ALMATY, NAS RK

A.Seitmuratov[1], B. Zhussipbek[1], G.Sydykova[1], A.Seithanova[2], U.Aitimova[3]

[1]The Korkyt Ata Kyzylorda State University, Kyzylorda;
[2]Innovative University of Eurasia, Pavlodar;
[3]SakenSeifullin Kazakh Agrotechnical University, Astana
angisin_@mail.ru, botik_80@mail.ru, sydykova77@mail.ru, ainur1179@mail.ru, zada@mail.ru

DYNAMIC STABILITY OF WAVE PROCESSES OF A ROUND ROD

Abstract: This paper is devoted to the study of the stability dynamics of wave processes of flat and circular elements, and also some axisymmetric problems of oscillation of an elastic layer limited by rigid or deformable boundaries when exposed to normal or rotational shear stresses are considered. Solutions to the problems under consideration were obtained using integral transformations by coordinate or time. The work develops the dynamic stability of a round rod. The loss of stability of a round rod will be investigated on the basis of the mathematical theory and the transverse oscillations of a round rod, described in the work of I.G. Philippov.

Key words: oscillations, stability, wave process, axisymmetric problems, round rod, exponential transformation, shear stress.

The issues of stability in a static formulation have been developed by many authors, and the results of such studies can be found in [1,2].

However, the issues of dynamic stability of elements' construction and structures received much less attention.

In this paper, the dynamic stability of a round rod is developed.

Consider a round elastic rod of length *l*. We will assume that an axial compressive force of intensity is applied to the ends of the rod at any moment of time.

The loss of stability of a round rod will be investigated on the basis of the mathematical theory and the transverse oscillation of a round rod, described in the work of I.G. Philippov [3].

The fourth order equation describing the transverse oscillation of the rod has the form.

$$A_0 \frac{\partial^4 V}{\partial t^4} - A_1 \frac{\partial^4 V}{\partial z^2 \partial t^2} + A_2 \frac{\partial^4 V}{\partial z^4} + \rho \frac{\partial^2 V}{\partial t^2} = F(z,t), \tag{1}$$

where the constants A_j are equal to

$$A_0 = \frac{\mu r_0^2 (4a^2 + b^2)}{8b^4 (a^2 - b^2)}; A_1 = \frac{\mu r_0^2 (13a^2 - 8b^2)}{8b^2 (a^2 - b^2)}; A_2 = \mu r_0^2, \tag{2}$$

r_0 - rod radius, a and b - propagation velocity of longitudinal and transverse waves in the material of the rod, μ - the module of shift модуль сдвига, ρ - rod material density.

Under the action of compressive force for a small period of time Δt when solving bending forces in cross-sectional planes of the rod ΔF, as we know, equals to [2]

$$\Delta F = \Delta P \frac{\partial^2 V}{\partial z^2} \tag{3}$$

Summing (3) over time, we get the power F :

$$F(z,t) = \int\limits_0^t P'(t-\xi) \frac{\partial^2 V}{\partial z^2} d\xi \tag{4}$$

where the lower limit of integration depends on the beginning of the force P and, for example if P power is applied at the $t = 0$ then the lower integration limit is also zero.

Obviously, if the compressive force is constant and is applied at the moment $t = 0$, then it can be written as $P = P_0 H(t)$, где $H(t)$ Heaviside function, then we get the following: (4)

$$F = -P_0 \frac{\partial^2 V}{\partial z^2} \tag{5}$$

Therefore, equation (5) can be written in the following form

$$A_0 \frac{\partial^4 V}{\partial t^4} - A_1 \frac{\partial^4 V}{dz^2 \partial t^4} + A_2 \frac{\partial^4 V}{\partial z^4} + \rho \frac{\partial^2 V}{\partial t^2} - \int\limits_0^t P'(t-\xi) \frac{\partial^2 V}{\partial z^2} d\xi = 0 \tag{6}$$

To study the stability of the rod, it is necessary to formulate the boundary conditions at the ends of the rod. These conditions are: hinged joints $V = \frac{\partial^2 V}{\partial z^2} = 0$, rigid fastening $V = \frac{\partial V}{\partial z} = 0$, free ending $\frac{1}{a^2} \frac{\partial^2 V}{\partial t^2} + 4 \frac{\partial^2 V}{\partial z^2} = 0; \frac{\partial^3 V}{\partial z^3} = 0.$ In order to study the stability of the rod, it is necessary to formulate the boundary conditions at the ends of the rod. These conditions are: hinged joints $V = \frac{\partial^2 V}{\partial z^2} = 0$, rigid fastening $V = \frac{\partial V}{\partial z} = 0$, free ending

$$\frac{1}{a^2} \frac{\partial^2 V}{\partial t^2} + 4 \frac{\partial^2 V}{\partial z^2} = 0; \frac{\partial^3 V}{\partial z^3} = 0.$$

The solution of equation (6) will be sought believing that

$$V(z,t) = V_0(z) \exp(i\omega t) \tag{7}$$

where ω is oscillation frequency. Putting (7) into the equation (6), for для V_0 we get the equation

$$A_2 \frac{d^4 V}{dz^4} + [A_1 \omega^4 - \int\limits_0^\infty P'(\xi) \exp(i\omega \xi) d\xi] \frac{d^2 V_0}{dz^2} + A_0 \omega^4 V_0 - \rho \omega^2 V_0 = 0 \tag{8}$$

Denoting by $Q(\omega)$ Fourier's exponential transform of rate of change of compressive force $P'(t)$, equation (8) we write in the form

$$\frac{d^4V_0}{dz^4} + B_0\frac{d^2V_0}{dz^2} + B_1V_0 = 0 \qquad (9)$$

where the coefficients are B_0, B_1 are equal to

$$B_0 = \frac{A_1\omega^2 - Q(\omega)}{A_2}; \qquad B_1 = \frac{A_0\omega^4 - \rho\omega^2}{A_2} \qquad (10)$$

For simplicity, we consider the case when the ends of the rod are hinged, i.e. at $z = 0$ and $z = l$ conditions are met

$$V = \frac{\partial^2 V}{\partial z^2} = 0 \qquad (11)$$

The solution of equation (9) is sought in the form of

$$V_0 = \sum_{n=1}^{\infty} V_{0n}\sin\left(\frac{\pi n}{l}z\right) \qquad (12)$$

at the same time, boundary conditions (11) are satisfied automatically.
Putting (12) into the equation (9) for the length $Q(\omega)$ we get

$$Q(\omega) = A_1\omega^2 - A_2\left(\frac{l}{\pi n}\right)^2\left[B_1 + \left(\frac{\pi n}{l}\right)^4\right] \qquad (13)$$

Введем безразмерные величины
Let's introduce dimensionless quantities

$$Q_0(\xi) = \frac{Q(\omega)}{\mu\pi^4}; \xi = \frac{\omega l}{\pi b}; c = \pi\left(\frac{r_0}{l}\right); \frac{b^2}{a^2} = \frac{1-2\upsilon}{2(1-\upsilon)} \qquad (14)$$

And then for $Q_0(\xi)$ we get

$$Q_0(\xi) = \frac{2}{c^2}\left[\frac{(9-5\upsilon)c^2 + 4}{9-10\upsilon}\right]\xi^2 - \xi^4 - \frac{8}{9-10\upsilon} \qquad (15)$$

where υ - Poisson's ratio.
     The physical meaning of the influence of the rate of change of the compressive force is that, it is important that the impulse of this force or the rate of increase of the force over time as in the impact theory.
     You can also consider other types of binding. For example, you can search for solutions of equation (9) in the form

$$V_0 = C_1 \left[\frac{\cos(\alpha_0 z)}{\alpha_0^n} + \frac{\cos(\alpha_1 z)}{\alpha_1^n} \right] + C_2 \left[\frac{\cos(\alpha_0 z)}{\alpha_0^n} - \frac{\cos(\alpha_1 z)}{\alpha_1^n} \right] +$$

$$+ C_3 \left[\frac{\sin(\alpha_0 z)}{\alpha_0^m} + \frac{\sin(\alpha_1 z)}{\alpha_1^m} \right] + C_4 \left[\frac{\sin(\alpha_0 z)}{\alpha_0^m} - \frac{\sin(\alpha_1 z)}{\alpha_1^m} \right] \tag{16}$$

where C_j - arbitrary constants, integers (n,m) are selected from conditions at $Z = 0$ и $Z = l$

$\grave{a}_j$ - the roots of the characteristic equation and are equal

$$a_j = \sqrt{\frac{B_0}{2} \pm \sqrt{\frac{B_0^2}{4} - B_1}}$$

In the case of rigid fastening of both ends of the rod integers $(n = 0, m = 1)$ and to find $Q(\omega)$ we get the transcendental equation

$$2 - \frac{\alpha_0^2 + \alpha_1^2}{\alpha_0 \alpha_1} \sin(\alpha_0 l) \sin(\alpha_1 l) - 2\cos(\alpha_0 l)\cos(\alpha_1 l) = 0, \tag{17}$$

Similarly, you can consider other combinations of conditions for binding the ends of the rod.

Some axisymmetric problems of oscillation of an elastic layer bounded by rigid or deformable boundaries when exposed to a normal or rotational shear stress are considered below. Solutions to the problems under consideration were obtained using integral transformations by coordinate or time.

First we consider the problem for half-space under the assumption that the half-space $z > 0$ is an anisotropic medium with the axis of symmetry of the mechanical properties (axis) (axis z), and the surface of which is subjected to an impulse voltage at the time $\xi_{z0} = -f(r,t)$.

Because of the symmetry of the mechanical properties of the medium relative to the axis z of the unique nonzero component of the displacement vector, $U_0(r,z,t)$ only the stresses and ξ_{r0} and ξ_{z0} the ones determined by formulas

$$\xi_{r0} = C_{nn} \left(\frac{\partial U_0}{\partial r} - \frac{U_0}{r} \right),$$

$$\xi_{z0} = C_{mm} \frac{\partial U_0}{\partial z} \tag{18}$$

The equation of motion reduces to one

$$\frac{\partial \xi_{r0}}{\partial r} + \frac{\partial \xi_{r0}}{\partial z} + \frac{2\xi_{r0}}{r} = \rho \frac{\partial^2 U_0}{\partial t^2} \tag{19}$$

Substituting the expressions for ξ_{r0} and ξ_{z0} from (18) into equation (19), we bring it to the form:

$$\frac{\partial^2 U_0}{\partial r^2} + \frac{1}{r} \frac{\partial U_0}{\partial r} - \frac{U_0}{r^2} + \gamma^2 \frac{\partial^2 U_0}{\partial z^2} = \frac{1}{b^2} \frac{\partial^2 U_0}{\partial t^2} \tag{20}$$

where

$$b^2 = \frac{C_{nn}}{\rho}; \quad \gamma^2 = \frac{C_{mm}}{C_{nn}}$$

If the half-space is isotropic, then $\gamma = 1$ and $b = \sqrt{\dfrac{\mu}{\rho}}$.

The boundary conditions for U_0 has:

$$\xi_{z0} = -f(r,t) \text{ under } z = 0, \ t \geq 0 \tag{21}$$
$$U_0 \to 0 \text{ under } z \to \infty \tag{22}$$

The initial conditions of the problem are zero

$$U_0 = \frac{\partial U_0}{\partial t} = 0 \qquad \text{under } t = 0 \tag{23}$$

The solution of equation (20) for the boundary (21) - (22) and the initial conditions (6) will be sought, by applying the Laplace transform. Suppose,

$$U(r,z,p) = \int_0^\infty U_0(r,z,t) e^{-pt} dt, \ \operatorname{Re} p > 0 \tag{24}$$

Definitely, for the function $U(r,z,p)$ we obtain the equation

$$\frac{\partial^2 U}{\partial r^2} + \frac{1}{r}\frac{\partial U}{\partial r} - \left(\frac{1}{r^2} + \frac{p^2}{b^2}\right) U + \gamma^2 \frac{\partial^2 U}{\partial z^2} = 0 \tag{25}$$

And U must satisfy the boundary conditions:

$$\frac{\partial U}{\partial z} = -\frac{f_0(r,p)}{C_{66}} \qquad \text{under } z = 0, \ t > 0 \tag{26}$$
$$U_0 \to 0 \text{ under } z \to \infty \tag{27}$$

where

$$f_0(r,p) = \int_0^\infty (r,t) e^{-pt} dt.$$

The general solution of equation (25) is sought by the method of separation of variables (the Fourier method) and has the form:

$$U(r,z,p) = \int_0^\infty \alpha \left[A(\alpha,p) e^{-\frac{z}{\gamma}\sqrt{\alpha^2 + \frac{p^2}{b^2}}} + B(\alpha,p) e^{\frac{z}{\gamma}\sqrt{\alpha^2 + \frac{p^2}{b^2}}} \right] J_1(\alpha r) d\alpha. \tag{28}$$

where $A(\alpha,p)$ and $B(\alpha,p)$ are defined from boundary conditions (26)-(27) from the condition (29) follows that

$$B(\alpha,p) = 0 \tag{29}$$

Using boundary condition (26), for defining $A(\alpha, p)$ we'll take integral equation:

$$\int\limits_0^\infty \alpha A(\alpha, p)\sqrt{\alpha^2 + \frac{p^2}{b^2}} J_1(\alpha r) d\alpha = \frac{\gamma}{C_{66}} f_0(r, p) \tag{30}$$

Let

$$f_0(r, p) = \int\limits_0^\infty \alpha f_1(\alpha, p) J_1(\alpha r) d\alpha \tag{31}$$

Then

$$A(\alpha, p) = \frac{\gamma f_1(\alpha, p)}{C_{mm}\sqrt{\alpha^2 + \frac{p^2}{b^2}}} \tag{32}$$

Substituting expression (29) and (32) into formula (28), we obtain the following expression:

$$U(r, z, p) = \frac{\gamma}{C_{mm}} \int\limits_0^\infty \frac{\alpha f_1(\alpha, p)}{\sqrt{\alpha^2 + \frac{p^2}{b^2}}} J_1(\alpha r) e^{-\frac{z}{\gamma}\sqrt{\alpha^2 + \frac{p^2}{b^2}}} d\alpha \tag{33}$$

We consider the special case when

$$f_0(r, p) = \frac{\varphi_0(p)}{r} \tag{34}$$

In case (34) function

$$f_1(\alpha, p) = \frac{\varphi_0(p)}{\alpha}$$

and (33) has

$$U(r,z,p) = \frac{\gamma}{C_{mm}} \int\limits_0^\infty \frac{\varphi_0(p)}{\sqrt{\alpha^2 + \frac{p^2}{b^2}}} e^{-\frac{z}{\gamma}\sqrt{\alpha^2 + \frac{p^2}{b^2}}} J_1(\alpha r) d\alpha = \frac{1}{C_{mm}} \varphi_0(p) I_{\frac{1}{2}}\left[\frac{p}{2b}\left(\sqrt{\frac{z^2}{\gamma^2} + r^2} - \frac{z}{\gamma}\right)\right] K_{\frac{1}{2}}\left[\frac{p}{2b}\left(\sqrt{\frac{z^2}{\gamma^2} + r^2} + \frac{z}{\gamma}\right)\right]$$

where $K_{\frac{1}{2}}, I_{\frac{1}{2}}$ Bessel functions of imaginary argument. Using the representations of the functions $I_{\frac{1}{2}}(\zeta)$ and $K_{\frac{1}{2}}(\zeta)$, for $U(r, z, p)$ we find that

$$U(r, z, p) = \frac{b\varphi_0(p)}{C_{mm} rp}\left[e^{-\frac{pz}{\gamma a}} - e^{-\frac{p}{a}\sqrt{\frac{z^2}{\gamma^2} + r^2}}\right] \tag{35}$$

Paying attention to the expression (35) in p, for the required value $U_0(r, z, t)$, we'll take the expression

$$U_0(r,z,t) = \frac{b}{\gamma C_{mm} r} \int_0^t f_1(t-\xi) \left[H\left(\xi - \frac{z}{\gamma b}\right) - H\left(\xi - \frac{1}{b}\sqrt{\frac{z^2}{\gamma^2} + r^2}\right) \right] d\xi \qquad (36)$$

where

$$f(r,t) = \frac{f_1(t)}{r}.$$

The resulting expression $U_0(r,z,t)$ consists of two terms, the first term corresponding to plane wave propagating in half-space with velocity γb and parallel to the plane $z = 0$, and the second term to the diffracted wave, which has the form of half-ellipsoid of revolution (hemisphere at $\gamma = 1$) and in contact with plane wave on the rotation axis at $z = b\gamma t$.

Besides, from (36) follows, that $U_0(r,z,t)$ fades out from r as $1/r$.

If the acting function $f(r,t)$ is arbitrary, then we represent it in the form of Schlemmich series:

$$f(r,t) = \frac{1}{r}\sum_{j=0}^{\infty} a_j(t) J_0(jr) = \frac{f_r(t)}{r} \qquad (37)$$

where

$$a_0(t) = \frac{1}{\pi}\int_0^\pi \left\{ f_r(0,t) + U\int_0^1 \frac{\frac{\partial f_r(\xi U,t)}{\partial r}}{\sqrt{1-\xi^2}} d\xi \right\} dU;$$

$$a_j(t) = \frac{2}{\pi}\int H\cos(jU)\left\{ \int_0^1 \frac{\frac{\partial f_r(\xi U,t)}{\partial r}}{\sqrt{1-\xi^2}} d\xi \right\} dU; j = 1,2,... \qquad (38)$$

For $f(r,t)$ type (37) function $f_1(\alpha, p)$, entering to the formula (33), is

$$f_1(\alpha, p) = \frac{1}{\alpha}\sum_{j=0}^{\infty} a_{j0}(p) H(\alpha - j) \qquad (39)$$

where

$$a_{j0}(p) = \int_0^\infty a_j(p) e^{-pt} dt. \qquad (40)$$

Following,

$$U(r,z,p) = \frac{\gamma}{C_{66}}\sum_{j=0}^{\infty} a_{j0}(p)\int_0^\infty \frac{e^{-\frac{z}{\gamma}\sqrt{\alpha^2 + \frac{p^2}{b^2}}}}{\sqrt{\alpha^2 + \frac{p^2}{b^2}}} J_1(\alpha r) d\alpha \qquad (41)$$

Paying attention (41) on p and using theory about convolution, we'll take

$$U_0\left(r,z,p\right)=\frac{\gamma}{2C_{66}}\sum_{j=0}^{\infty}\int_{g}^{t}a_j\left(t-\xi\right)T_j\left(r,z,\xi\right)d\xi \tag{42}$$

where

$$T_j\left(r,z,\xi\right)=b\int_{j}^{\infty}J_1\left(\alpha r\right)J_0\left[\alpha\sqrt{b^2t^2-\frac{z^2}{\gamma^2}}\right]d\alpha \tag{43}$$

А.Ж.Сейтмұратов[1], Б.К.Жүсіпбек[1], Г.К.Сыдыкова[1], А.Сейтжанова[2], У.Ж.Айтимова[3]

[1]Қорқыт Ата атындағы Қызылорда мемлекеттік университеті, Қызылорда;
[2]Инновациялық Еуразия университеті, Павлодар;
[3]С.Сейфуллин атындағы Қазақ агротехникалық университеті, Астана;

ДӨҢГЕЛЕК ӨЗЕКТІҢ ТОЛҚЫНДЫҚ ПРОЦЕСТЕРІНІҢ ДИНАМИКАЛЫҚ ТҰРАҚТЫЛЫҒЫ

Аннотация. Бұл жұмыс жазық және айналмалы элементтердің толқындық процестерінің орнықтылық динамикасын зерттеуге арналған, сондай-ақ мақалада қалыпты немесе айналмалы жанасу кернеулерінің әсер етуі кезінде қатты немесе деформацияланатын шекаралармен шектелген серпімді қабат тербелісінің кейбір осесимметриялық есептері қарастырылады. Қарастырылатын есептердің шешімдері координат бойынша немесе уақыт бойынша интегралды түрлендірулерді пайдалана отырып алынған. Жұмыста дөңгелек өзектің динамикалық тұрақтылығы жайлы есепбін терең зеріттеледі. Дөңгелек өзектің орнықтылығының ауытқуы И. Г. Филипповтың жұмысында баяндалғандай, дөңгелек өзектің көлденең тербелісі математикалық теория негізінде зерттелетін болады.

Түйін сөз: тербелістер, орнықтылық, толқындық процесс, осесимметриялық есептер, дөңгелек өзек, экспоненциалды түрлендіру, жанама кернеу.

А.Ж.Сейтмуратов[1], Б.К.Жусипбек[1], Г.К.Сыдыкова[1], А.Сейтжанова[2], У.Ж.Айтимова[3]

[1]Кызылординский государственный университет им.Коркыт Ата, Кызылорда;
[2]Инновационный Евразийский университет, Павлодар;
[3]Казахский агротехнический университет имени Сакена Сейфуллина,Астана

ДИНАМИЧЕСКАЯ УСТОЙЧИВОСТЬ ВОЛНОВЫХ ПРОЦЕССОВ КРУГЛОГО СТЕРЖНЯ

Аннотация: Данная работа посвящена изучению динамики устойчивости волновых процессов плоских и круговых элементов, а также рассматривается некоторые осесимметричные задачи колебания упругого слоя ограниченные жесткими или деформируемыми границами при воздействии на него нормального или вращательного касательного напряжений. Решения рассматриваемых задач получены с использованием интегральных преобразований по координате или по времени. В работе развивается динамическая устойчивость круглого стержня. Потеря устойчивости круглого стержня будет исследоваться на основе математической теории и поперечного колебания круглого стержня, изложенной в работе И.Г.Филиппова.

Ключевые слова: колебания, устойчивость, волновой процесс, осесимметричные задачи, круглый стержнь, экспоненциальное преобразование, касательная напряжения.

Information about authors:
Seitmuratov Angisin – Doktor of Physical and Matematical Sciences, Professoz, The Korkyt Ata Kyzylorda State University. Kyzylorda.
Zhussipbek Botagoz Kunibekkyzy- senior lecturer of the Department «Information communication technologies».Master of computer science, The Korkyt Ata Kyzylorda State University, Kyzylorda.
Sydykova Gulnar- Candidate of technical sciences, head of Department, The Korkyt Ata Kyzylorda State University. Kyzylorda.
Ainur Seitkhanova - Innovative University of Eurasia Associate Professor of the Department "Energy and Metallurgy", PhD –Mechanics. Pavlodar
Aitimova Ulzada Zholdasbekovna- Senior Lecturer of the Department "Information Systems", Candidate of Physical and Mathematical Sciences, SakenSeifullin Kazakh Agrotechnical University

REFERENCES

[1] Filippov I.G., S.I. Filippov 1995. Dynamic stability theory of rods. Proceedings of the Russian-Polish seminar. Theoretical Foundations of construction. Warsaw, pp.63 -69.

[2] Filippov, I.G., 1979. An approximate method for solving dynamic viscoelastic media. PMM, 43(1): 133 -137.

[3] Filippov I.G., S.I Filippov V.I. Kostin 1995. Dynamics of two-dimensional composites. - Proceedings of the International Conference on Mechanics and Materials, USA, Los Angeles, pp.75 -79.

[4] Seitmuratov,A; Medeubaev N., Yeshmurat,G., Kudebayeva,G. Approximate solution of the an elastic layer vibration task being exposed of moving load. News of the national academy of sciences of the republic of Kazakhstan-Series physic-mathematical. Том: 2 Выпуск: 318 Стр.: 54-60. 2018.

[5] Seitmuratov,A.Z., Nurlanova B.M., Medeubaev N., Equetions of vibration of a two-dimensionally layered plate strictly based on the decision of various boundaty-value problems. Bulletin of the Karaganda university-mathematics. Том: 87 Выпуск: 3 Стр.: 109-116. 2017.

[6] Seitmuratov A.,Yergalauova Z., Makhambayeva, Bexeitova A. Axismetric problems of elastic layer oscillation limited by rigid or deformed boundries. News of the national academy of sciences of the republic of Kazakhstan-Series of geology and technical sciences. Выпуск: 1 Стр.:127-135. 2018 .

[7] Seitmuratov Z., Medeubaev N.K., Madelhanova A.Z., Kainbaeva L.S., Djuzbaeva, A.M. Decisions of equalization of vibrations of hyperbolic type by the of decomposition method. 2017- News of the National Academy of Sciences of the Republic of Kazakhstan, Series of Geology and Technical Sciences

[8] Seytmuratov A.Z., Zharylgapova D.M., Medeubaev N.K., Ibraeva, A.A. Applied tasks of plates fluctuation under more difficult boundary conditions .2017- News of the National Academy of Sciences of the Republic of Kazakhstan, Series of Geology and Technical Sciences.

[9] Seitmuratov A., Ramazanov M., Medeubaev N., Kaliev B. Mathematical theory of vibration of elastic or viscoelastic plates, under non-stationary external influences 2017- News of the National Academy of Sciences of the Republic of Kazakhstan, Series of Geology and Technical Sciences.

[10] Ashirbayev N., Ashirbayeva Zh., Sultanbek T., Shomanbayeva M. Waves of elastic stresses in the doublyconnected domain. Вестник КарГУ, серия математика, 2018, №2 (90), с.18-25.

[11] Seitmuratov A., Zharmenova B., Dauitbayeva A., Bekmuratova A. K., Tulegenova E., Ussenova G. Numerical analysis of the solution of some oscillation problems by the decomposition method. News of the National academy of sciences of the Republic of Kazakhstan. Series physic-mathematical. ISSN 1991-346X https://doi.org/10.32014/2019.2518-1726.4 Volume 1, Number 323 (2019), 28 – 37.

Publication Ethics and Publication Malpractice
in the journals of the National Academy of Sciences of the Republic of Kazakhstan

For information on Ethics in publishing and Ethical guidelines for journal publication see http://www.elsevier.com/publishingethics and http://www.elsevier.com/journal-authors/ethics.

Submission of an article to the National Academy of Sciences of the Republic of Kazakhstan implies that the described work has not been published previously (except in the form of an abstract or as part of a published lecture or academic thesis or as an electronic preprint, see http://www.elsevier.com/postingpolicy), that it is not under consideration for publication elsewhere, that its publication is approved by all authors and tacitly or explicitly by the responsible authorities where the work was carried out, and that, if accepted, it will not be published elsewhere in the same form, in English or in any other language, including electronically without the written consent of the copyright-holder. In particular, translations into English of papers already published in another language are not accepted.

No other forms of scientific misconduct are allowed, such as plagiarism, falsification, fraudulent data, incorrect interpretation of other works, incorrect citations, etc. The National Academy of Sciences of the Republic of Kazakhstan follows the Code of Conduct of the Committee on Publication Ethics (COPE), and follows the COPE Flowcharts for Resolving Cases of Suspected Misconduct (http://publicationethics.org/files/u2/New_Code.pdf). To verify originality, your article may be checked by the Cross Check originality detection service http://www.elsevier.com/editors/plagdetect.

The authors are obliged to participate in peer review process and be ready to provide corrections, clarifications, retractions and apologies when needed. All authors of a paper should have significantly contributed to the research.

The reviewers should provide objective judgments and should point out relevant published works which are not yet cited. Reviewed articles should be treated confidentially. The reviewers will be chosen in such a way that there is no conflict of interests with respect to the research, the authors and/or the research funders.

The editors have complete responsibility and authority to reject or accept a paper, and they will only accept a paper when reasonably certain. They will preserve anonymity of reviewers and promote publication of corrections, clarifications, retractions and apologies when needed. The acceptance of a paper automatically implies the copyright transfer to the National Academy of Sciences of the Republic of Kazakhstan.

The Editorial Board of the National Academy of Sciences of the Republic of Kazakhstan will monitor and safeguard publishing ethics.